

GESCHAKELDE VOEDING 66W TRIPLE OUTPUT +5/+12/-5V 6.0/2.5/0.5A

€ 33,95

Excl. BTW: € 28,06

Afbeeldingen



Beschrijving

Universal AC input / Full range
Protections: Short circuit / Overload / Over voltage
Cooling by free air convection
LED indicator for power on
100% full load burn-in test
All using 105C long life electrolytic capacitors
Withstand 300VAC surge input for 5 second
High operating temperature up to 70
Withstand 5G vibration test
High efficiency, long life and high reliability

OUTPUT:

DC VOLTAGE +5V - +12V - -5V

RATED CURRENT 6A - 2.8A - 0.5A

CURRENT RANGE 0 ~ 8A - 0.2 ~ 3.5A - 0 ~ 1A

RATED POWER 66.1W

RIPPLE & NOISE (max.) 80mVp-p - 120mVp-p - 80mVp-p

OUTPUT VOLTAGE ADJ. RANGE CH1 4.75 ~ 5.5V

INPUT:

VOLTAGE RANGE 90 ~ 264VAC 125 ~ 373VDC

FREQUENCY RANGE 47 ~ 63Hz

PROTECTION:

OVER LOAD 110 ~ 150% rated output power

Protection type :

Hiccup mode, recovers automatically after fault condition is

OVER VOLTAGE 5.75 ~ 6.75V

Protection type :

Hiccup mode, recovers automatically after fault condition is removed

Dimensions 129*98*38mm (L*W*H)

Productinformatie

Artikelnummer	RT65A
Merk	MEANWELL
Is on Sale	Nee

