

**GESCHAKELDE VOEDING 68W TRIPLE OUTPUT +5/+12/+24V 4.0/1.5/1.0A**

**€ 33,95**

Excl. BTW: € 28,06

**Afbeeldingen**



**Beschrijving**

- Universal AC input / Full range
- Protections: Short circuit / Overload / Over voltage
- Cooling by free air convection
- LED indicator for power on
- 100% full load burn-in test
- All using 105C long life electrolytic capacitors
- Withstand 300VAC surge input for 5 second
- High operating temperature up to 70
- Withstand 5G vibration test
- High efficiency, long life and high reliability

OUTPUT:

DC VOLTAGE +5V - +24V - +12V

RATED CURRENT 4A - 1.5A - 1.0A

CURRENT RANGE 0.5 ~ 8A - 0.2 ~ 3.0A - 0.1 ~ 1A

RATED POWER 66.1W

RIPPLE & NOISE (max.) 80mVp-p - 120mVp-p - 80mVp-p

OUTPUT VOLTAGE ADJ. RANGE CH1 4.75 ~ 5.5V

INPUT:

VOLTAGE RANGE 90 ~ 264VAC 125 ~ 373VDC

FREQUENCY RANGE 47 ~ 63Hz

PROTECTION:

OVER LOAD 110 ~ 150% rated output power

Protection type :

Hiccup mode, recovers automatically after fault condition is

OVER VOLTAGE 5.75 ~ 6.75V

Protection type :

Hiccup mode, recovers automatically after fault condition is removed

Dimensions 129\*98\*38mm (L\*W\*H)

## Productinformatie

---

Artikelnummer	RT65D
Merk	MEANWELL
Is on Sale	Nee

