
PLAFONDSPEAKER 20/10/5W 100V 2-WEG SYSTEEM (RAL9010)

€ 92,50

Excl. BTW: € 76,45

Afbeeldingen



Beschrijving

17 cm (6.5") HiFi-ceiling speaker with corrosion free grille, suitable for the installation in suspended ceilings of any material. Equipped with a 2-way coaxial driver. Quick snap-in mounting due to round ceiling cut-out through which the speaker with transformer and mounting ring can be installed. A push-terminal block allows a quick and easy connection to the 100-V-network including the eventually necessary level adjustment (transformer version). A quick-mounting bayonet connection provides an easy installation of the grille.

DL 18/2 can be supplied painted in other RAL colours on request.

Speaker cabinet systems for ceilings are available for these speakers from KAISER, 58579 Schalksmühle, Germany. The KompaX cabinet is suitable for the DL 18/1 and DL 18/2, Art. nos. 1293-15, 1293-00, 1292-35, 1292-00, 1294-15 and 1294-00 in conjunction with the front ring Art. no. 1293-20. Fire protection housing systems (F30) are available (FlamoX).

Typical applications:

- For fitting in hollow ceilings, for music and speech in shops, at home, hotels etc.

Attributes:

- Moisturised cone
- UV-resistant
- Metal basket, non-corrodible
- functionally at low temperature according to EN 60068-2-1 (-40 °C; 96 h)
- up to the standards of the Germanischer Lloyd (requirements for electrical equipment / low temperature)

Transformer matching 20; 10; 5 W
Sound pressure level 94 dB (1 W/1 m)
@ 4954 Hz
Frequency response 50- 20000 Hz
Mean sound pressure level 90 dB (1 W/1 m)
Max. sound pressure level 103 dB (20 W/1 m)
Opening angle (-6 dB) 64°/4000 Hz
Resonance frequency f_s 90 Hz
Magnetic induction 0,95 T
Magnetic flux 310 μ Wb
Height of front pole-plate 3 mm
Voice coil diameter 25 mm
Height of winding 6 mm
Cutout diameter 200 mm
Net weight 1,5 kg
Protective system IP X3
Temperature range -40 ... 80 °C
Colour RAL 9010

Productinformatie

Artikelnummer	DL18/2/100
Merk	VISATON
Is on Sale	Nee

