

SPEAKER BREEDBAND 4OHM 4W/10W 150-20000HZ 84DB 50X50MM

€ 13,95

Excl. BTW: € 11,53

Afbeeldingen



Beschrijving

cm (2") fullrange speaker with square basket, soft surround and special light weight cone. Balanced frequency response above 250 Hz, brilliant highs and good omnidirectional sound distribution. Suitable as midrange driver in column speaker systems for HiFi applications as well as for 100 V sound reinforcement systems. Due to the small size also suitable for model construction and as control speaker for electronic devices.

- Rated power 4 W
- Maximum power 10 W
- Nominal impedance Z 4 Ohm
- Frequency response 150- 20000 Hz
- Mean sound pressure level 84 dB (1 W/1 m)
- Opening angle (-6 dB) 180°/4000 Hz
- Excursion limit +/-2 mm
- Resonance frequency f_s 250 Hz
- Magnetic induction 0,75 T
- Magnetic flux 65 μ Wb
- Height of front pole-plate 2 mm
- Voice coil diameter 14 mm
- Height of winding 2,7 mm
- Cutout diameter 45 mm
- Net weight 0,1 kg
- D.C. resistance Rdc 3,6 Ohm

Mechanical Q factor Qms 2,48
Electrical Q factor Qes 2,5
Total Q factor Qts 1,24
Equivalent volume Vas 0,2 l
Effective piston area Sd 12 cm²
Dynamically moved mass Mms 0,5 g
Force factor Bxl 1,1 Tm
Inductance of the voice coil L 0,08 mH
Temperature range -25 ... 70 °C

Productinformatie

Artikelnummer	FRWS5/4
Merk	VISATON
Is on Sale	Nee

