


**SPEAKER BREEDBAND 8OHM 2W/5W 200-20000HZ 80DB 50X50MM
AFGESCHERMD**

€ 16,95

Excl. BTW: € 14,01

Afbeeldingen



Beschrijving

Magnetically shielded 5 cm (2") full-range driver with highly compact construction due to light-weight alnico magnet. Features balanced frequency response from 350 Hz and good omnidirectional sound distribution. Particularly suitable for music and voice reproduction in multimedia applications such as TV's, PC's etc.

Technical Data:

Rated power 4 W

Maximum power 8 W

Nominal impedance Z 8 Ohm

Frequency response 200- 20000 Hz

Mean sound pressure level 80 dB (1 W/1 m)

Opening angle (-6 dB) 180°/4000 Hz

Excursion limit +/-2 mm

Resonance frequency fs 350 Hz

Voice coil diameter 14 mm

Height of winding 3,5 mm

Cutout diameter 45 mm

Net weight 0,052 kg

D.C. resistance Rdc 7,2 Ohm

Mechanical Q factor Qms 4,1

Electrical Q factor Qes 9,35

Total Q factor Qts 2,85

Equivalent volume Vas 0,2 l

Effective piston area Sd 12 cm²

Dynamically moved mass Mms 0,5 g

Force factor Bxl 1 Tm

Inductance of the voice coil L 0,1 mH

Temperature range -25 ... 70 °C

Productinformatie

Artikelnummer	FRWS5SC
Merk	VISATON
Is on Sale	Nee

