

SPEAKER BREEDBAND 8 OHM 20/30W 100-13000HZ 90DB 102X102MM

€ 12,25

Excl. BTW: € 10,12

Afbeeldingen



Beschrijving

10 cm (4") fullrange speaker with high efficiency and balanced frequency response. Especially suitable as control speaker for electronic devices.

Typical applications:

- Control speakers for electronic devices
- Ceiling- mounted speakers in railway carriages and busses
- Model construction

Technical Data:

Rated power 20 W

Maximum power 30 W

Nominal impedance Z 8 Ohm

Frequency response 100- 13000 Hz

Mean sound pressure level 90 dB (1 W/1 m)

Opening angle (-6 dB) 92°/4000 Hz

Excursion limit +/-1,5 mm

Resonance frequency fs 188 Hz

Magnetic induction 0,95 T
Magnetic flux 135 μ Wb
Height of front pole-plate 3 mm
Voice coil diameter 15 mm
Height of winding 4 mm
Cutout diameter 93 mm
Net weight 0,16 kg
D.C. resistance Rdc 7,2 Ohm
Mechanical Q factor Qms 6,27
Electrical Q factor Qes 2,92
Total Q factor Qts 1,99
Equivalent volume Vas 1,7 l
Effective piston area Sd 56 cm²
Dynamically moved mass Mms 2 g
Force factor Bxl 2,0 T m
Inductance of the voice coil L 0,5 mH
Connections 5,2 x 0,5 mm (+)
2,8 x 0,5 mm (-)
Temperature range -25 ... 70 °C

Productinformatie

Artikelnummer	R10S/8
Merk	VISATON
Is on Sale	Nee

