

**SPEAKER BREEDBAND 200-15000HZ 50OHM 2/3W 60MM
VOCHTBESTENDIG**

€ 8,25

Excl. BTW: € 6,82

Afbeeldingen



Beschrijving

.4 cm (2.5\") full-range speaker with a plastic basket and plastic diaphragm. Broad frequency response and good voice reproduction. Particularly well suited to outdoor applications and where ambient conditions are generally unfavourable (e.g. high humidity).

Typical applications:

- Monitoring speaker for electronic devices
- Monitoring speaker for outdoor systems

Technical Data:

Rated power 2 W

Maximum power 3 W

Nominal impedance Z 50 Ohm

Frequency response 200- 15000 Hz

Mean sound pressure level 86 dB (1 W/1 m)

Opening angle (-6 dB) 109°/4000 Hz

Excursion limit +/-1,5 mm

Resonance frequency f_s 300 Hz

Magnetic induction 0,7 T

Magnetic flux 45 μ Wb

Height of front pole-plate 2 mm

Voice coil diameter 10 mm

Height of winding 2,5 mm

Cutout diameter 60 mm

Net weight 0,05 kg

Protective system IP 65 *)

Temperature range -40 ... 80 °C

Productinformatie

Artikelnummer	K64WP/50
Merk	VISATON
Is on Sale	Nee

