

SPEAKER HOOG 4 OHM 60/100W 1700-22000HZ 86DB 30MM PER PAAR

€ 41,95

Excl. BTW: € 34,67

Afbeeldingen



Beschrijving

Very compact 13 mm (0.5") ferro-fluid cooled tweeter with a polycarbonate cone, featuring an absolutely linear frequency response. Crisp high-range reproduction and excellent omnidirectional sound distribution. Tweeter in low to medium-output 2- or 3-way systems or as an additional tweeter. Can be surface or flush mounted. Especially suitable for mounting in confined spaces (e.g. mirror vicinity and door handles).

Accessories: Mounting ring and connecting cables included

Nominal power handling with high pass 60 W (12 dB/Okt.; 6000 Hz)

Peak power handling with high pass 100 W (12 dB/Okt.; 6000 Hz)

Nominal impedance Z 4 Ohm

Frequency response 1700- 22000 Hz

Mean sound pressure level 86 dB (1 W/1 m)

Opening angle (-6 dB) 180°/8000 Hz

Resonance frequency f_s 2400 Hz

Magnetic induction 0,8 T

Magnetic flux 65 μ Wb

Voice coil diameter 13 mm

Height of winding 1,5 mm

Cutout diameter 33,5 mm

Net weight 0,026 kg

D.C. resistance R_{dc} 3,3 Ohm

Inductance of the voice coil L 0,4 mH

Productinformatie

Artikelnummer	CP13
Merk	VISATON
Is on Sale	Nee

