

ACCULADER 14,4V 60A VOOR LEAD-ACID ACCU'S

€ 459,95

Excl. BTW: € 380,12

Afbeeldingen



Beschrijving

Features

- 2/8 stage charger for lead acid batteries
- Universal AC input / Full range
- Built-in active PFC function
- 2/8 stage charger selected by switch
- Relay contacts for \"Charging ok\" and \"Output ok\"
- Protection: reverse polarity/short circuit/over voltage/over temperature
- Built-in remote ON-OFF control
- 3 color LED loading indicator

Operating Temperature: -20...+60°C

Storage Temperature: -40...+85°C

Insulation Voltage

I/P-O/P: 3000V AC

I/P-FG: 1500V AC

O/P-FG: 500V AC

Insulation Resistance

I/P-O/P, I/P-FG, O/P-FG: 500V DC: 100MΩ

Dimensions: 300x184x70mm

Weight: 3,50kg

I/P = Input, O/P = Output, FG = Frame Ground

Input

Input Voltage: 90...264VAC 47...63Hz

AC Current (230V): 5.2A

In-Rush Current, Cold Start (230V): 50A

Output

Boost Charge Voltage: 14,4V

Float Charge Voltage: 13,6V

Output Current, max: 60A

Efficiency: 85%

Recommended Battery Capacity: 200...600Ah

Productinformatie

Artikelnummer	PB100012
Merk	MEANWELL
Is on Sale	Nee

