

**GESCHAKELDE VOEDING SINGLE OUTPUT 76W 48V/1.6A**

**€ 31,50**

Excl. BTW: € 26,03

**Afbeeldingen**



**Beschrijving**

MODEL RS-75-48

OUTPUT:

DC VOLTAGE 48V

RATED CURRENT 1.6A

CURRENT RANGE 0 ~ 1.6A

RATED POWER 76.8W

RIPPLE & NOISE (max.) 200mVp-p

OUTPUT VOLTAGE ADJ. RANGE 42 ~ 54V

VOLTAGE TOLERANCE +/-1.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-0.5%  
SETUP, RISE TIME 500ms, 30ms/230VAC  
HOLD TIME (Typ.) 60ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC  
FREQUENCY RANGE 47 ~ 63Hz  
EFFICIENCY(Typ.) 86%  
AC CURRENT (Typ.) 1.2A/230VAC  
INRUSH CURRENT (Typ.) COLD START 40A/230VAC  
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power  
Protection type : Hiccup mode, recovers automatically after fault condition is removed  
OVER VOLTAGE 55.2 ~ 64.8V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 129\*97\*38mm (L\*W\*H)

## Productinformatie

---

Artikelnummer	RS7548
Merk	MEANWELL
Is on Sale	Nee

