

DIN-RAIL VOEDING 100W 27.6V/2,25A MET ACCULADER EN UPS FUNCTIE

€ 62,50

Excl. BTW: € 51,65

Afbeeldingen



Beschrijving

Universal AC input / Full range

EProtections: Short circuit / Overload / Over voltage

EBattery low protection / Battery reverse polarity protection
by fuse

ECan be installed on DIN rail TS-35/7.5 or 15

EAlarm signal for AC OK and Battery low
via TTL open collector, optional via relay)

ECooling by free air convection

EPass LPS
ELED indicator for power on
E100% full load burn-in test

DRC-100 is a 100W AC/DC DIN rail type security power supply series. In addition to the primary output, there is a charger output with a smaller rated current, enabling the backup power supply application the security access systems require. DRC-100 accepts the universal input between 90VAC and 264VAC, and supplies 13.8VDC and 27.6VDC at output, respectively. With the efficiency up to 88%, it can operate with air convection cooling under -30 through 70 . In addition to the key protection features ç] ç] such as overload protection, over voltage protection, battery low cut off, and battery reverse polarity protection (by fuse), the alarm signal for AC OK and battery low signaling is provided, via TTL open collector output for the standard model (via relay contact output as the optional model), to facilitate the system design.

Vermogen : : 100W

Uitgang 1

dc spanning : 27,6V

Stroom (max.) : 2.25A

Spanning instelbaar 24 ~ 30V

Ripple & Noise (max.) : 240mVp-p

Uitgang 2

dc spanning : 27,6V

Stroom (max.) : 1.25A

Ingang spanning : 90 ~ 264VAC 127 ~ 370VDC

Frequentie : 47 ~ 63Hz

Productinformatie

Artikelnummer	DRC100B
Merk	MEANWELL
Is on Sale	Nee

