

ADAPTER 24V 1500MA GESCHAKELD

€ 24,50

Excl. BTW: € 20,25

Afbeeldingen



Beschrijving

Features

- Plug-in switching power supply with europlug
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Insulation Class II
- Low no load power consumption

Technical Specifications

| | |
|----------------------------------|--------------------------|
| Input Voltage: | 90...264V AC (47...63Hz) |
| | 135...370V DC |
| Input Inrush Current, Max.: | 60A |
| No Load Power Consumption, Max.: | 0,3W |

| | |
|------------------------|-------------|
| Operating Temperature: | -20...+50°C |
| Cable Length: | 1m |
| Input Plug: | Euro |
| Output Plug, Coax: | 2,1x5,5mm |
| Weight: | 226g |

1" align="center" valign="top">84,5

| Part Nr. | U_A | I_A | P_A | DU_A | U_{RN} | h |
|--------------------|-------|---------|-------|--------|----------------------|------|
| | [V] | [A] | [W] | [%] | [mV _{p-p}] | [%] |
| GS36E24-P1J | 24 | 0...1,5 | 36 | 2 | 180 | 85,5 |

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | PSS2415 |
| Merk | MEANWELL |

