

MEERPOLIG STEKER 7P FEMALE IP68

€ 7,95

Excl. BTW: € 6,57

Afbeeldingen



Contact arrangement and open for cable construction						
Number of contacts	2	3	4	5	6	7
Male contact size (mm)	1.27	1.27	1.27	1.27	1.27	1.27
Panel diameter (mm)	20.00	20.00	20.00	20.00	20.00	20.00
Panel depth (mm)	20.00	20.00	20.00	20.00	20.00	20.00
Panel depth (mm)	20.00	20.00	20.00	20.00	20.00	20.00
Panel depth (mm)	20.00	20.00	20.00	20.00	20.00	20.00
Panel depth (mm)	20.00	20.00	20.00	20.00	20.00	20.00
Panel depth (mm)	20.00	20.00	20.00	20.00	20.00	20.00
Panel depth (mm)	20.00	20.00	20.00	20.00	20.00	20.00
Panel depth (mm)	20.00	20.00	20.00	20.00	20.00	20.00
Panel depth (mm)	20.00	20.00	20.00	20.00	20.00	20.00

Beschrijving

Features

- Cliffcon® 68 is an IP68 rated multipin connector for waterproof and rugged applications
- IP68 for under water, outdoor and indoor
- 2 to 9 gold-plated contacts (no 8 pin version)
- Fixing thread M15
- Panel hole cut-out 13mm Ø
- FM 686800: sealing cap for socket FM68680_ (must be ordered separately)

Technical Specifications

Connector Locking System:

Screw

Connection Type	Solder
Degree of Protection:	IP68
Mechanical Operating Life, Min.:	500 Cycles
Temperature Range:	-25...+85°C
Insulation Resistance:	20000Ohm
Material of Contact:	CuZn, Gold-plated
Material of Housing:	Nylon 66 ¹⁾
Cable Diameter (Female Plug):	5...8mm

¹⁾fire resistance: V-O

Socket	Pole	U_N	I_N	Contact Ø	R_C
	[A]	[V AC]	[A]	[mm]	[Ohm]
FM686802	2	250	13	1,6x2	2
FM686803	3	250	13	1,6x3	2
FM686804	4	200	5	1x4	5
FM686805	5	180	5	1x5	5
FM686806	6	125	5	1x6	5
FM686807	7	125	5	1y7	5
FM686809	9	125	3	0,7x9	10

U_N = Rated Voltage, I_N = Rated Current, R_C = Contact Resistance

Productinformatie

Artikelnummer	FM686817
Merk	CLIFF

