


SOLENOID HOUDMAGNEET RVS 24VDC/0.135A 14KG

€ 39,95

Excl. BTW: € 33,02

Afbeeldingen



Beschrijving

Features

- Holding magnets
- Completely encapsulated stainless steel housing
- Under side with threaded holes
- Min. 200mm connecting lead
- Internal thread M4



Technical Specifications

| Part Nr. | U_N | I_N | P_N | F_H | $\varnothing \times L$ | Weight |
|------------|--------|-------|-------|-------|------------------------|--------|
| ITS-MSM_ | [V DC] | [A] | [W] | [N] | [mm] | [g] |
| 2520-12-VA | 12 | 0,27 | 3,2 | 140 | 25x20 | 60 |
| 2520-24-VA | 24 | 0,13 | 3,2 | 140 | 25x20 | 60 |
| 3222-12-VA | 12 | 0,30 | 3,6 | 240 | 32x22 | 110 |
| 3222-24-VA | 24 | 0,15 | 3,6 | 240 | 32x22 | 110 |

U_N = Voltage, I_N = Current, P_N = Power at 100%ED, F_H = Typical Force



Coil Data

| Part Nr. | ED _{rel} | ED _{max.} | P _{max.} |
|----------|-------------------|--------------------|-------------------|
| ITS-MSM_ | [%] | [sec] | [W] |
| 2520_-VA | 100 | infinite | 3,2 |
| 3222_-VA | 100 | infinite | 3,6 |

ED_{Rel} = Duty Cycle, ED_{Max.} = Duty Cycle, Max., P_{Max.} = Capacity, Max. (20°C)



Dimensions

| Part Nr. | a | b | c | d | e |
|----------|------|----|----|---|-----|
| ITS-MSM_ | [mm] | | | | |
| 2520_-VA | 25 | 20 | M4 | 6 | 200 |
| 3222_-VA | 32 | 22 | M4 | 6 | 200 |

Productinformatie

| | |
|---------------|---------------|
| Artikelnummer | MSM2520-24 |
| Merk | RED-MAGNETICS |

