


NEOPIXEL RING - 24 X WS2812 5050 RGB LED WITH INTEGRATED DRIVER

€ 12,95

Excl. BTW: € 10,70

Afbeeldingen



Beschrijving

Round and round and round they go! 24 ultra bright smart LED NeoPixels are arranged in a circle with 2.6" (66mm) outer diameter. The rings are 'chainable' - connect the output pin of one to the input pin of another. Use only one microcontroller pin to control as many as you can chain together! Each LED is addressable as the driver chip is inside the LED. Each one has ~18mA constant current drive so the color will be very consistent even if the voltage varies, and no external choke resistors are required making the design slim. Power the whole thing with 5VDC and you're ready to rock.

There is a single data line with a very timing-specific protocol. Since the protocol is very sensitive to timing, it requires a real-time microcontroller such as an AVR, Arduino, PIC, mbed, etc. It cannot be used with a Linux-based microcomputer or interpreted microcontroller such as the netduino or Basic Stamp. Our wonderfully-written [Neopixel library for Arduino supports these pixels!](#) As it requires hand-tuned assembly it is only for AVR cores but others may have ported this chip driver code so please google around. An 8MHz or faster processor is required.

Voltage: DC 5V

LED source: WS2812B 5050

Light color: RGB

LED quantity: 24led

Board color: black,

Artikelnummer	NPS24
Merk	Brand

