

## GESCHAKELDE VOEDING SINGLE OUTPUT 1008W 48V/21A 1HE

€ 335,00

Excl. BTW: € 276,86

### Afbeeldingen



### Beschrijving

Universal AC input / Full range  
AC input active surge current limiting  
Built-in 5V/0.5A auxiliary power  
Built-in active PFC function, PF>0.95  
Protections: Short circuit / Overload / Over voltage / Over temperature  
Output voltage can be trimmed between 40 ~ 110% of the rated output voltage  
Forced air cooling by built-in DC fan  
High power density 10.7w/inch  
1U low profile 41mm  
Active current sharing up to 4000W(3+1)  
DC OK Signal  
Built-in remote ON-OFF control  
Built-in remote sense function

OUTPUT  
DC VOLTAGE: 48V

RATED CURRENT: 21A  
CURRENT RANGE: 0 ~ 21A  
RATED POWER: 1008W  
VOLTAGE ADJ. RANGE: 43 ~ 55V

#### INPUT

VOLTAGE RANGE: 90 ~ 264VAC  
FREQUENCY RANGE: 47 ~ 63Hz  
POWER FACTOR (Typ.): 0.95/230VAC  
EFFICIENCY (Typ.): 83%  
AC CURRENT (Typ.): 6A/230VAC  
INRUSH CURRENT (Typ.): 40A/230VAC  
LEAKAGE CURRENT: <2.0mA / 240VAC

## Productinformatie

---

Artikelnummer	RSP100048
Merk	MEANWELL
Is on Sale	Nee

