

**LASDOOS MET GEL 180X69X40MM VOOR KABEL VAN 9-22MM 3 X 1,5-5X  
6,0MM<sup>2</sup>**

**€ 47,50**

Excl. BTW: € 39,26

**Afbeeldingen**



**Beschrijving**

**Features**

- Moulding shell: One piece, coloured, re-openable, impact-proof, flame retardant (UL94 VO)
- Filled with Relicon non-toxic gel, high dielectric strength
- No mixing, easy to install
- UV, ageing and weather resistant
- Unlimited shelf life
- With connector, ready for assembly
- Certified according to:
  - DIN EN 50393 (corresponds to DIN VDE 0278-393)
  - DIN EN 60695-2-11 (corresponds to VDE 0471-2-11)

**Application**

RELICON Relifix gel technology offers several advantages. It is quick and easy to install. The moulding shells are provided with a film hinge and are made from thick-walled, tough and impact resistant polypropylene (PP). The Relicon gel in the shells insulates and seals the complete connection as the joint is closed. Depending on the connector type, Relifix can be used as a universal straight-through or branch joint. It is suitable for jointing on polymeric cables and wires made of PVC, XLPE, PE, EPR etc.

Application: In low-voltage electrical networks as straight-through and/or branch joint, e.g. underground, submerged, outdoor, indoor and wiring ducts.

Cable Diameter Main Cable	9-22 mm
Conductor Cross Section Main Cable (max.)	5 x 16 mm <sup>2</sup>
Conductor Cross Section Main Cable (min.)	3 x 6 mm <sup>2</sup>
Connector	Connector block
Height (H)	40 mm
Length (L)	180 mm
Width (W)	69 mm

## Productinformatie

---

Artikelnummer	RMGO45
Merk	Brand

