

**AANSLUITKLEM GROEN/GEEL 4.2MM VOOR 35MM DINRAIL MAX.
2.5MM2KLEM AANSLUITING**

€ 3,50

Excl. BTW: € 2,89

Afbeeldingen



Beschrijving

Name	Value	Unit
Total number of connection points	2	
Total number of potentials	1	
Color	green-yellow	
Ratings according to 1	IEC/EN 60947-7-2	
Connection technology	Push-in CAGE CLAMP®	
Number of connection points	2	
Actuation type	Betätigungswerkzeug	

Connectable conductor materials	Kupfer	
Nominal cross section	1.5 mm ²	
Solid sizes	0.25 ... 2.5 mm ² / 22 ... 14 AWG	
solid, directly pluggable	0.5 ... 2.5 mm ² / 20 ... 14 AWG	
Fine-stranded wires	0.25 ... 2.5 mm ² / 22 ... 14 AWG	
min. fine-stranded with insulated ferrule, push-in terminati	0.75 mm ² / 18 AWG	
Strip length	9 ... 11 mm / 0.35 ... 0.43 in	
Type of wiring	Front-entry wiring	
Design	horizontal	
Marking level	Center/Side marking	
Insulating material	Polyamide 66 (PA 66)	
Fire load [MJ]	0.074	MJ
Weight [g]	6.669	g
Width	4.2 mm / 0.165 in	
Height from upper-edge of DIN-rail	32.9 mm / 1.295 in	
Length	50.8 mm / 2 in	
Type of mounting	DIN-35 rail	

Productinformatie

Artikelnummer	AKDR30GG
Merk	Brand

