

MINI MD LED DRIVER 16-28VDC 700MA 20W DIMBAAR


€ 22,51

Excl. BTW: € 18,60

Afbeeldingen



Model	Output Power (W)	Input Voltage (VDC)	Output Current (mA)	Efficiency (%)	Temp. Rise (°C)	Weight (g)	Dimensions (mm)
MD-01	10	16-28	700	85	10	1.5	10x10x10
MD-02	20	16-28	700	85	10	3.5	10x10x15
MD-03	30	16-28	700	85	10	5.5	10x10x20
MD-04	40	16-28	700	85	10	7.5	10x10x25
MD-05	50	16-28	700	85	10	9.5	10x10x30
MD-06	60	16-28	700	85	10	11.5	10x10x35
MD-07	70	16-28	700	85	10	13.5	10x10x40
MD-08	80	16-28	700	85	10	15.5	10x10x45
MD-09	90	16-28	700	85	10	17.5	10x10x50
MD-10	100	16-28	700	85	10	19.5	10x10x55



Beschrijving



EIJLANDER
the best in electronics!

Features

- IP20 independent driver, for indoor use (MINI MD).
- Class II protection against electric shock for direct or indirect contact (MINI MD).
- Driver for built-in use (MINI MD BI).
- It can be used for lighting equipment in protection class I and II (MINI MD BI).
- Active Power Factor Corrector.
- Current regulation $\pm 8\%$ including temperature variations.
- Supplied with terminal cover and cable retainer (MINI MD).
- Input and output terminal blocks on the same side (wire cross-section up to 1,5 mm² / AWG15).
- Clamping screws on primary and secondary circuits for cables with diameter: min. 3 mm - max. 8 mm (MINI MD).
- Driver can be secured with slot for screws.
- Protections:
 - against overheating and short circuits;
 - against mains voltage spikes;
 - against overloads.
- Thermal protection = C.5.a.

Productinformatie

Artikelnummer	127035
Merk	TCI

