

GESCHAKELDE VOEDING 5.0V 3.0A 15W PRINT MONTAGE

€ 14,96

Excl. BTW: € 12,36

Afbeeldingen



Beschrijving

Features

- Enclosed type for PCB mounting
- Universal input
- Protections: short circuit and over load
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
	120...370V DC
Input Inrush Current, Max.:	40A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight:	59g

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
IRM-15-3.3	3,3	0...3,5	11,55	2,5	200	74
IRM-15-5	5	0...3	15	2,5	200	78
IRM-15-12	12	0...1,25	15	2,5	200	82
IRM-15-15	15	0...1	15	2,5	200	82
IRM-15-24	24	0...0,63	15,12	2,5	200	83

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Norms

TÜV EN60950-1, UL60950-1

Approvals



Productinformatie

Artikelnummer	IRM1505
Merk	MEANWELL

