

GESCHAKELDE VOEDING SINGLE OUTPUT 26W 24V/1.1A

€ 16,50

Excl. BTW: € 13,64

Afbeeldingen



Beschrijving

Note

These power supplies are considered as a component that has to be installed in a final equipment.

Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Long life 105°C electrolytic capacitors

Technical Specifications

Input Voltage:	88...264V AC (47...63Hz)
	125...373V DC
Input Inrush Current, Max.:	30A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	+10/-5%
Over Load Protection:	110...180%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-20...+70°C
Weight:	200g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
RS-25-3.3	3,3	0...6	19,8	3	80	73,5
RS-25-5	5	0...5	25	2	80	78,5
RS-25-12	12	0...2,1	25,2	1	120	81,5
RS-25-15	15	0...1,7	25,5	1	120	83,5
RS-25-24	24	0...1,1	26,4	1	120	86
RS-25-48	48	0...0,57	27,36	1	200	85

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Labelling

Productinformatie

Artikelnummer	RS2524
Merk	MEANWELL

