

## LED DRIVER 25W 16-24V/1050MA CC DIMBAAR

€ 24,95

Excl. BTW: € 20,62

### Afbeeldingen



### Beschrijving

#### Features

- PCD-25: AC dimmable, for leading edge and trailing edge dimmers, flexible wire terminals
- PLD-25: not AC dimmable, flexible wire terminals
- Plastic enclosure IP30
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Suitable for LED lighting and moving sign applications
- Constant current
- EN61000-3-2, Class C, EN55015, EN61347-1, EN61347-2-13



#### Technical Specifications



#### Input Voltage

PCD-25:	180...295V AC (47...63Hz)
PLD-25:	90...295V AC (47...63Hz)

Input Inrush Current, Max.	
PCD-25:	10A
PLD-25:	25A
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-30...+60°C
Weight:	190g

I/P = Input, O/P = Output



Part Nr.	$U_A$	$I_A$	$P_A$	$U_{RN}$	h
	[V]	[mA]	[W]	[V <sub>p-p</sub> ]	[%]
PCD-25-350B	40...58	0...350	20,3	4,6	82
PCD-25-700B	24...36	0...700	25,2	2,7	81
PCD-25-1050B	16...24	0...1050	25,2	2,2	80,5
PCD-25-1400B	12...18	0...1400	25,2	2	80
PLD-25-350	40...58	0...350	20,3	4,6	85
PLD-25-700	24...36	0...700	25,2	2,7	86
PLD-25-1050	16...24	0...1050	25,2	2,2	85
PLD-25-1400	12...18	0...1400	25,2	2	84

$U_A$  = Output Voltage Range,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{RN}$  = Ripple & Noise, h = Typ. Efficiency



## Productinformatie

Artikelnummer	PCD251050B
Merk	MEANWELL

