

LED VOEDING 24V/5.00A 120W IP67 BEHUIZING PWM

€ 69,50

Excl. BTW: € 57,44

Afbeeldingen



Beschrijving

Features

- Universal input
- Plastic enclosure IP67
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Suitable for LED lighting and moving sign applications
- PWM output voltage
- Dimming function (external voltage 1...10V DC, PWM)
- EN61000-3-2, Class C, EN55015, EN61347-1, EN61347-2-13

Technical Specifications

Input Voltage:	90...305V AC (47...63Hz)
	127...431V DC
Input Inrush Current, Max.:	60A
Over Load Protection:	108...120%
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-40...+70°C
Weight:	970g

I/P = Input, O/P = Output

Part Nr.	U_A	I_A	P_A	DU_A	h
	[V]	[A]	[W]	[%]	[%]
PWM-120-12	12	10	120	4	88
PWM-120-24	24	5	120	4	90
PWM-120-36	36	3,4	122,4	2	90
PWM-120-48	48	2,5	120	1	90,5

U_A = Output Voltage, I_A = Output Current, P_A = Output Power, DU_A = Output Voltage Tolerance, h = Typ. Efficiency

Note

Suitable for indoor use and outdoor use without direct sunlight exposure. Please avoid immerse in the water over 30 minutes. These power supplies are considered as a component that has to be installed in a final equipment.

Productinformatie

Artikelnummer	PWM12024
Merk	MEANWELL

