


LED DRIVER 36-72V/2100MA 150W IP67 BEHUIZING

€ 49,95

Excl. BTW: € 41,28

Afbeeldingen



Beschrijving

Features

- Universal input
- Plastic enclosure IP67
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Protection Class 2
- Fixed output current

Technical Specifications

| | |
|------------------------------|---------------------------|
| Input Voltage: | 180...305V AC (47...63Hz) |
| | 254...431V DC |
| Input Inrush Current, Max.: | 40A |
| Withstand Voltage (I/P-O/P): | 3000V AC |
| Operating Temperature: | -25...+50°C |
| Weight: | 740g |

I/P = Input, O/P = Output

| Part Nr. | U_A | I_A | P_A | DI_A | U_{RN} | h |
|--------------|-----------|-------|-------|--------|---------------------|-----|
| | [V] | [mA] | [W] | [%] | [V _{p-p}] | [%] |
| LPC-150-350 | 215...430 | 350 | 150,5 | 5 | 2 | 90 |
| LPC-150-500 | 150...300 | 500 | 150 | 5 | 1,5 | 90 |
| LPC-150-700 | 107...215 | 700 | 150,5 | 5 | 1 | 90 |
| LPC-150-1050 | 72...144 | 1050 | 151,2 | 5 | 1 | 90 |
| LPC-150-1400 | 54...108 | 1400 | 151,2 | 5 | 1 | 90 |
| LPC-150-1750 | 43...86 | 1750 | 150,5 | 5 | 1 | 90 |
| LPC-150-2100 | 36...72 | 2100 | 151,2 | 5 | 1 | 90 |
| LPC-150-2450 | 31...62 | 2450 | 151,9 | 5 | 1 | 90 |
| LPC-150-2800 | 27...54 | 2800 | 151,2 | 5 | 1 | 90 |
| LPC-150-3150 | 24...48 | 3150 | 151,2 | 5 | 1 | 90 |

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DI_A = Output Current Tolerance, U_{RN} = Ripple & Noise, h = Typ. Efficiency

Note

Devices only for use in equipment with another primary purpose such as photocopiers, overhead projectors and slide projectors or for scale illumination or indication purposes.
Suitable for indoor use and outdoor use without direct sunlight exposure. Please avoid immerse in the water over 30 minutes.

Productinformatie

| | |
|---------------|------------|
| Artikelnummer | LPC1502100 |
| Merk | MEANWELL |

