

**DC MAXI JOLLY HC BI DALI LED DRIVER 26-48VDC 1050-2100MA
55W110X76X30MM 1-10V & PUSH**

€ 79,00

Excl. BTW: € 65,29

Afbeeldingen



Beschrijving



EIJLANDER
the best in electronics!

Features

- Multipower driver supplied with dip-switch for the selection of the output current.

- IP20 independent driver, for indoor use

(DC MAXI JOLLY HC/2 DALI).

- Class I protection against electric shock for direct or indirect contact (DC MAXI JOLLY HC/2 DALI).

- Driver for built-in use (DC MAXI JOLLY HC DALI BI).

- It can be used for lighting equipment in protection class I.

- Active Power Factor Corrector.

- Analogical input (NTC) for thermal sensor connection.

- Auxiliary output 12 V max. 100 mA.

- Current regulation $\pm 5\%$ including temperature variations.

- Input and output terminal blocks on the same side

(wire cross-section up to 1,5 - 2,5 mm² / AWG15 - AWG13).

- Clamping screws on primary and secondary circuits for cables

with diameter: min. 3 mm - max. 8 mm (DC MAXI JOLLY HC/2

DALI).

- Protections:

- against overheating and short circuits;

- against mains voltage spikes;
- against overloads.
- Thermal protection = C.5.a.

Productinformatie

Artikelnummer	123417
Merk	TCI
Is on Sale	Nee

