

GESCHAKELDE VOEDING 5.0V 6.00A 30W KROONSTEEN AANSLUITING

€ 21,95

Excl. BTW: € 18,14

Afbeeldingen



Beschrijving

Features

- Enclosed type
- IRM-30-_: for PCB mounting
- IRM-30-_ST: for screw terminal mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

Technical Specifications

| | |
|----------------------------------|---------------------------|
| Input Voltage: | 85...264V AC (47...440Hz) |
| Input Inrush Current, Max.: | 45A |
| No Load Power Consumption, Max.: | 0,1W |
| Withstand Voltage: | 3000V AC |
| Operating Temperature: | -30...+70°C |
| Weight | |
| IRM-30-_: | 109g |
| IRM-30-_ST: | 120g |

| Part Nr. | U_A | I_A | P_A | DU_A | U_{RN} | h |
|-------------|-------|----------|-------|--------|----------------------|------|
| | [V] | [A] | [W] | [%] | [mV _{p-p}] | [%] |
| IRM-30-5 | 5 | 0...6 | 30 | 2,5 | 120 | 83 |
| IRM-30-12 | 12 | 0...2,5 | 30 | 2,5 | 150 | 88 |
| IRM-30-15 | 15 | 0...2 | 30 | 2,5 | 200 | 88 |
| IRM-30-24 | 24 | 0...1,3 | 31,2 | 2,5 | 240 | 88,5 |
| IRM-30-48 | 48 | 0...0,63 | 30,2 | 2,5 | 300 | 90 |
| IRM-30-5ST | 5 | 0...6 | 30 | 2,5 | 120 | 83 |
| IRM-30-12ST | 12 | 0...2,5 | 30 | 2,5 | 150 | 88 |
| IRM-30-15ST | 15 | 0...2 | 30 | 2,5 | 200 | 88 |

| | | | | | | |
|-------------|----|----------|------|-----|-----|------|
| IRM-30-24ST | 24 | 0...1,3 | 31,2 | 2,5 | 240 | 88,5 |
| IRM-30-48ST | 48 | 0...0,63 | 30,2 | 2,5 | 300 | 90 |

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Norms

TÜV EN60950-1, UL60950-1

Approvals



Productinformatie

| | |
|---------------|-----------|
| Artikelnummer | IRM3005ST |
| Merk | MEANWELL |

