

GESCHAKELDE VOEDING 5.0V 4.0A 20W PRINT MONTAGE

€ 16,50

Excl. BTW: € 13,64

Afbeeldingen



Beschrijving

Features

- Enclosed type for PCB mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
	120...370V DC
Input Inrush Current, Max.:	40A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight:	50g

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
IRM-20-3.3	3,3	0...4,5	14,85	2,5	200	76
IRM-20-5	5	0...4	20	2,5	200	79
IRM-20-12	12	0...1,8	21,6	2,5	200	84
IRM-20-15	15	0...1,4	21	2,5	200	84
IRM-20-24	24	0...0,9	21,6	2,5	200	85

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Norms

TÜV EN60950-1, UL60950-1

Productinformatie

Artikelnummer	IRM2005
Merk	MEANWELL

