

**GESCHAKELDE VOEDING 15.0V 1.00A 15W PRINT MONTAGE**

**€ 14,96**

Excl. BTW: € 12,36

**Afbeeldingen**



**Beschrijving**

**Features**

- Enclosed type for PCB mounting
- Universal input
- Protections: short circuit and over load
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

## Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
	120...370V DC
Input Inrush Current, Max.:	40A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight:	59g

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
IRM-15-3.3	3,3	0...3,5	11,55	2,5	200	74
IRM-15-5	5	0...3	15	2,5	200	78
IRM-15-12	12	0...1,25	15	2,5	200	82
IRM-15-15	15	0...1	15	2,5	200	82
IRM-15-24	24	0...0,63	15,12	2,5	200	83

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Norms

TÜV EN60950-1, UL60950-1

## Approvals



## Productinformatie

Artikelnummer	IRM1515
Merk	MEANWELL

