

## GESCHAKELDE VOEDING 15.0V 4.0A 60W PRINT MONTAGE

€ 23,50

Excl. BTW: € 19,42

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed type
- IRM-60-\_: for PCB mounting
- IRM-60-\_ST: for screw terminal mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

#### Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
Input Inrush Current, Max.:	60A
No Load Power Consumption, Max.:	0,1W

Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight	
IRM-60-_:	195g
IRM-60-_ST:	228g

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	$h$
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
IRM-60-5	5	0...10	50	2,5	80	84
IRM-60-12	12	0...5	60	2,5	120	87,5
IRM-60-15	15	0...4	60	2,5	120	89
IRM-60-24	24	0...2,5	60	2,5	150	90
IRM-60-48	48	0...1,25	60	2,5	240	91
IRM-60-5ST	5	0...10	50	2,5	80	84
IRM-60-12ST	12	0...5	60	2,5	120	87,5
IRM-60-15ST	15	0...4	60	2,5	120	89
IRM-60-24ST	24	0...2,5	60	2,5	150	90
IRM-60-48ST	48	0...1,25	60	2,5	240	91

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Norms

TÜV EN60950-1, UL60950-1

## Approvals



## Productinformatie

---

Artikelnummer	IRM6015
Merk	MEANWELL

