

GESCHAKELDE VOEDING 24.0V 1.90A 45W KROONSTEEN AANSLUITING

€ 24,95

Excl. BTW: € 20,62

Afbeeldingen



Beschrijving

Features

- Enclosed type
- IRM-45-_: for PCB mounting
- IRM-45-_ST: for screw terminal mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
Input Inrush Current, Max.:	60A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight	
IRM-45-_:	195g
IRM-45-_ST:	228g

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
IRM-45-5	5	0...8	40	2,5	80	83,5
IRM-45-12	12	0...3,8	45,6	2,5	150	87,5
IRM-45-15	15	0...3	45	2,5	180	88,5
IRM-45-24	24	0...1,9	45,6	2,5	200	89,5
IRM-45-48	48	0...0,94	45,12	2,5	300	90,5
IRM-45-5ST	5	0...8	40	2,5	80	83,5
IRM-45-12ST	12	0...3,8	45,6	2,5	150	87,5
IRM-45-15ST	15	0...3	45	2,5	180	88,5

IRM-45-24ST	24	0...1,9	45,6	2,5	200	89,5
IRM-45-48ST	48	0...0,94	45,12	2,5	300	90,5

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Norms

TÜV EN60950-1, UL60950-1

Approvals



Productinformatie

Artikelnummer	IRM4524ST
Merk	MEANWELL

