

GESCHAKELDE VOEDING 12.0V 2.50A 30W PRINT MONTAGE

€ 19,95

Excl. BTW: € 16,49

Afbeeldingen



Beschrijving

Features

- Enclosed type
- IRM-30-\_: for PCB mounting
- IRM-30-\_ST: for screw terminal mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

## Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
Input Inrush Current, Max.:	45A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight	
IRM-30-_:	109g
IRM-30-_ST:	120g

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
IRM-30-5	5	0...6	30	2,5	120	83
IRM-30-12	12	0...2,5	30	2,5	150	88
IRM-30-15	15	0...2	30	2,5	200	88
IRM-30-24	24	0...1,3	31,2	2,5	240	88,5
IRM-30-48	48	0...0,63	30,2	2,5	300	90
IRM-30-5ST	5	0...6	30	2,5	120	83
IRM-30-12ST	12	0...2,5	30	2,5	150	88
IRM-30-15ST	15	0...2	30	2,5	200	88

IRM-30-24ST	24	0...1,3	31,2	2,5	240	88,5
IRM-30-48ST	48	0...0,63	30,2	2,5	300	90

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Norms

TÜV EN60950-1, UL60950-1

## Approvals



## Productinformatie

Artikelnummer	IRM3012
Merk	MEANWELL

