

GESCHAKELDE VOEDING 12.0V 3.80A 45W PRINT MONTAGE

€ 20,95

Excl. BTW: € 17,31

Afbeeldingen



Beschrijving

Features

- Enclosed type
- IRM-45-\_: for PCB mounting
- IRM-45-\_ST: for screw terminal mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

## Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
Input Inrush Current, Max.:	60A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight	
IRM-45-_:	195g
IRM-45-_ST:	228g

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
IRM-45-5	5	0...8	40	2,5	80	83,5
IRM-45-12	12	0...3,8	45,6	2,5	150	87,5
IRM-45-15	15	0...3	45	2,5	180	88,5
IRM-45-24	24	0...1,9	45,6	2,5	200	89,5
IRM-45-48	48	0...0,94	45,12	2,5	300	90,5
IRM-45-5ST	5	0...8	40	2,5	80	83,5
IRM-45-12ST	12	0...3,8	45,6	2,5	150	87,5
IRM-45-15ST	15	0...3	45	2,5	180	88,5

IRM-45-24ST	24	0...1,9	45,6	2,5	200	89,5
IRM-45-48ST	48	0...0,94	45,12	2,5	300	90,5

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

### Norms

TÜV EN60950-1, UL60950-1

### Approvals



### Productinformatie

Artikelnummer	IRM4512
Merk	MEANWELL

