

**GESCHAKELDE VOEDING 15.0V 3.0A 45W PRINT MONTAGE**

**€ 20,95**

Excl. BTW: € 17,31

**Afbeeldingen**



**Beschrijving**

**Features**

- Enclosed type
- IRM-45-\_: for PCB mounting
- IRM-45-\_ST: for screw terminal mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

## Technical Specifications

|                                  |                           |
|----------------------------------|---------------------------|
| Input Voltage:                   | 85...264V AC (47...440Hz) |
| Input Inrush Current, Max.:      | 60A                       |
| No Load Power Consumption, Max.: | 0,1W                      |
| Withstand Voltage:               | 3000V AC                  |
| Operating Temperature:           | -30...+70°C               |
| Weight                           |                           |
| IRM-45-_:                        | 195g                      |
| IRM-45-_ST:                      | 228g                      |

| Part Nr.    | $U_A$ | $I_A$    | $P_A$ | $DU_A$ | $U_{RN}$             | h    |
|-------------|-------|----------|-------|--------|----------------------|------|
|             | [V]   | [A]      | [W]   | [%]    | [mV <sub>p-p</sub> ] | [%]  |
| IRM-45-5    | 5     | 0...8    | 40    | 2,5    | 80                   | 83,5 |
| IRM-45-12   | 12    | 0...3,8  | 45,6  | 2,5    | 150                  | 87,5 |
| IRM-45-15   | 15    | 0...3    | 45    | 2,5    | 180                  | 88,5 |
| IRM-45-24   | 24    | 0...1,9  | 45,6  | 2,5    | 200                  | 89,5 |
| IRM-45-48   | 48    | 0...0,94 | 45,12 | 2,5    | 300                  | 90,5 |
| IRM-45-5ST  | 5     | 0...8    | 40    | 2,5    | 80                   | 83,5 |
| IRM-45-12ST | 12    | 0...3,8  | 45,6  | 2,5    | 150                  | 87,5 |
| IRM-45-15ST | 15    | 0...3    | 45    | 2,5    | 180                  | 88,5 |

|             |    |          |       |     |     |      |
|-------------|----|----------|-------|-----|-----|------|
| IRM-45-24ST | 24 | 0...1,9  | 45,6  | 2,5 | 200 | 89,5 |
| IRM-45-48ST | 48 | 0...0,94 | 45,12 | 2,5 | 300 | 90,5 |

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Norms

TÜV EN60950-1, UL60950-1

## Approvals



## Productinformatie

|               |          |
|---------------|----------|
| Artikelnummer | IRM4515  |
| Merk          | MEANWELL |

