

GESCHAKELDE VOEDING 24.0V 1.30A 30W KROONSTEEN AANSLUITING

€ 21,95

Excl. BTW: € 18,14

Afbeeldingen



Beschrijving

Features

- Enclosed type
- IRM-30-_: for PCB mounting
- IRM-30-_ST: for screw terminal mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
Input Inrush Current, Max.:	45A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight	
IRM-30-_:	109g
IRM-30-_ST:	120g

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
IRM-30-5	5	0...6	30	2,5	120	83
IRM-30-12	12	0...2,5	30	2,5	150	88
IRM-30-15	15	0...2	30	2,5	200	88
IRM-30-24	24	0...1,3	31,2	2,5	240	88,5
IRM-30-48	48	0...0,63	30,2	2,5	300	90
IRM-30-5ST	5	0...6	30	2,5	120	83
IRM-30-12ST	12	0...2,5	30	2,5	150	88
IRM-30-15ST	15	0...2	30	2,5	200	88

IRM-30-24ST	24	0...1,3	31,2	2,5	240	88,5
IRM-30-48ST	48	0...0,63	30,2	2,5	300	90

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Norms

TÜV EN60950-1, UL60950-1

Approvals



Productinformatie

Artikelnummer	IRM3024ST
Merk	MEANWELL

