

**GESCHAKELDE VOEDING 24.0V 0.90A 20W PRINT MONTAGE**

**€ 16,50**

Excl. BTW: € 13,64

**Afbeeldingen**



**Beschrijving**

**Features**

- Enclosed type for PCB mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

## Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
	120...370V DC
Input Inrush Current, Max.:	40A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight:	50g

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
IRM-20-3.3	3,3	0...4,5	14,85	2,5	200	76
IRM-20-5	5	0...4	20	2,5	200	79
IRM-20-12	12	0...1,8	21,6	2,5	200	84
IRM-20-15	15	0...1,4	21	2,5	200	84
IRM-20-24	24	0...0,9	21,6	2,5	200	85

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Norms

TÜV EN60950-1, UL60950-1

## Productinformatie

---

Artikelnummer	IRM2024
Merk	MEANWELL

