

GESCHAKELDE VOEDING 48.0V 1.25A 60W KROONSTEEN AANSLUITING

€ 25,95

Excl. BTW: € 21,45

Afbeeldingen



Beschrijving

Features

- Enclosed type
- IRM-60-_: for PCB mounting
- IRM-60-_ST: for screw terminal mounting
- Universal input
- Protections: short circuit/over load/over voltage
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
Input Inrush Current, Max.:	60A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC

Operating Temperature:	-30...+70°C
Weight	
IRM-60-_:	195g
IRM-60-__ST:	228g

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
IRM-60-5	5	0...10	50	2,5	80	84
IRM-60-12	12	0...5	60	2,5	120	87,5
IRM-60-15	15	0...4	60	2,5	120	89
IRM-60-24	24	0...2,5	60	2,5	150	90
IRM-60-48	48	0...1,25	60	2,5	240	91
IRM-60-5ST	5	0...10	50	2,5	80	84
IRM-60-12ST	12	0...5	60	2,5	120	87,5
IRM-60-15ST	15	0...4	60	2,5	120	89
IRM-60-24ST	24	0...2,5	60	2,5	150	90
IRM-60-48ST	48	0...1,25	60	2,5	240	91

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Norms

TÜV EN60950-1, UL60950-1

Approvals



Productinformatie

Artikelnummer	IRM6048ST
Merk	MEANWELL

