


GESCHAKELDE VOEDING SINGLE OUTPUT 70W 5V/14A

€ 23,95

Excl. BTW: € 19,79

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low profile
- EN60335-1 (PD3), EN61558-1, -2, -16



Technical Specifications



Input Voltage:

85...264V AC (47...63Hz)

120...373V DC

Input Inrush Current, Max.:	65A
Leakage Current, Max.:	0,75mA
Output Voltage Adjustment:	±10%
Over Load Protection:	110...150%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	1250V AC
Operating Temperature:	-30...+70°C
Operating Altitude, Max.:	5000m
Weight:	300g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
LRS-75-5	5	0...14	70	2	100	86,5
LRS-75-12	12	0...6	72	1	120	89
LRS-75-15	15	0...5	75	1	120	89
LRS-75-24	24	0...3,2	76,8	1	150	90
LRS-75-36	36	0...2,1	75,6	1	200	91,5
LRS-75-48	48	0...1,6	76,8	1	200	91,5

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	LRS7505
Merk	MEANWELL

