

DC-DC CONVERTER 17-31V:12V 16.7A IN BEHUIZING

€ 135,00

Excl. BTW: € 111,57

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Overload protection
- Wide input voltage range 2:1
- DC decoupling of input and output
- Input/output insulation 4000V DC
- Regulated output voltage
- LED indicator for power on
- Short-circuit proof

Technical Specifications

Input Voltage:	See Table
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	4000V DC
I/P-FG:	2500V DC
O/P-FG:	2500V DC
Operating Temperature:	-40...+55°C
Weight:	940g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_E [V]	U_A [V]	I_A [A]	DU_A [%]	U_{RN} [mV _{p-p}]	h [%]
RSD-200B-12	16,8...31,2	12	0...16,7	±2	120	89
RSD-200B-24	16,8...31,2	24	0...8,4	±2	150	89
RSD-200B-48	16,8...31,2	48	0...4,2	±2	180	89
RSD-200C-12	33,6...62,4	12	0...16,7	±2	120	91
RSD-200C-24	33,6...62,4	24	0...8,4	±2	150	91
RSD-200C-48	33,6...62,4	48	0...4,2	±2	180	91
RSD-200D-12	67,2...143,0	12	0...16,7	±2	120	91

RSD-200D-24	67,2...143,0	24	0...8,4	±2	150	91
RSD-200D-48	67,2...143,0	48	0...4,2	±2	180	91

U_E = Input Voltage, U_A = Output Voltage, I_A = Output Current Range, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Labelling



Productinformatie

Artikelnummer	RSD200B12
Merk	MEANWELL
Is on Sale	Nee

