

---

**DC-DC CONVERTER 67-143V:48V 4.2A IN BEHUIZING**

**€ 135,00**

Excl. BTW: € 111,57

**Afbeeldingen**

---



**Beschrijving**

---

**Features**

- Enclosed case, screw terminals
- Overload protection
- Wide input voltage range 2:1
- DC decoupling of input and output
- Input/output insulation 4000V DC
- Regulated output voltage
- LED indicator for power on
- Short-circuit proof

## Technical Specifications

Input Voltage:	See Table
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	4000V DC
I/P-FG:	2500V DC
O/P-FG:	2500V DC
Operating Temperature:	-40...+55°C
Weight:	940g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	$U_E$ [V]	$U_A$ [V]	$I_A$ [A]	$DU_A$ [%]	$U_{RN}$ [mV <sub>p-p</sub> ]	$h$ [%]
RSD-200B-12	16,8...31,2	12	0...16,7	±2	120	89
RSD-200B-24	16,8...31,2	24	0...8,4	±2	150	89
RSD-200B-48	16,8...31,2	48	0...4,2	±2	180	89
RSD-200C-12	33,6...62,4	12	0...16,7	±2	120	91
RSD-200C-24	33,6...62,4	24	0...8,4	±2	150	91
RSD-200C-48	33,6...62,4	48	0...4,2	±2	180	91
RSD-200D-12	67,2...143,0	12	0...16,7	±2	120	91

RSD-200D-24	67,2...143,0	24	0...8,4	±2	150	91
RSD-200D-48	67,2...143,0	48	0...4,2	±2	180	91

$U_E$  = Input Voltage,  $U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Labelling



## Productinformatie

Artikelnummer	RSD200D48
Merk	MEANWELL
Is on Sale	Nee

