

VENTILATOR 5V/DC VAPOLAGER 17X17X8MM 1,5M3/H 21.5DB

€ 11,50

Excl. BTW: € 9,50

Afbeeldingen



Beschrijving

Design



Motor:	Patented One-phase Single Coil
	DC Brushless Motor Design
Nr. of Motor Poles:	8
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-O)

Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	AWG28, Stripped, Tinned



Technical Specifications



Rated Voltage:	5V DC
Operating Voltage:	2,5...6V DC
Dielectric Strength at 65% r. F.:	500V AC for 1 Min.
Insulation Resistance at 500V DC:	>500MOhm
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C



Part Nr.	U_{Rated}	P_{Airflow}	Noise	I	P_{el}	Speed
	[V]	[m ³ /h]	[dBA]	[A]	[W]	[RPM]
MC17080V1-A99	5	1,53	25	0,16	0,8	20000
MC17080V2-A99	5	1,19	16	0,1	0,5	15000

P_{Airflow} = Airflow, P_{el} = Rated Power and Current Tolerance, ±15%

Productinformatie

Artikelnummer	FO501708MC
Merk	SUNON
Is on Sale	Nee

