

**VENTILATOR 5V/DC VAPOLAGER 25X25X6MM 3,7M3/H 18DB**

**€ 8,65**

Excl. BTW: € 7,15

**Afbeeldingen**



**Beschrijving**

**Design**

Motor:	Patented One-phase Single Coil
	DC Brushless Motor Design
Nr. of Motor Poles:	8
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-0)
Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	AWG28, Stripped, Tinned

## Technical Specifications

Rated Voltage:	5V DC
Operating Voltage:	2,5...6V DC
Dielectric Strength at 65% r. F.:	500V AC for 1 Min.
Insulation Resistance at 500V DC:	>500MΩ
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C

Part Nr.	$U_{\text{Rated}}$	$P_{\text{Airflow}}$	Noise	I	$P_{\text{el}}$	Speed
	[V]	[m <sup>3</sup> /h]	[dBA]	[A]	[W]	[RPM]
<b>MC25060V2-A99</b>	5	3,74	23	0,075	0,38	10000

$P_{\text{Airflow}}$  = Airflow,  $P_{\text{el}}$  = Rated Power and Current Tolerance, ±15%

## Productinformatie

Artikelnummer	F0502506VD
Merk	SUNON

