

VENTILATOR 12V/DC VAPOLAGER 25X25X10MM 5,9M3/H 23DB

€ 11,01

Excl. BTW: € 9,10

Afbeeldingen



Beschrijving

Design



Motor:

Patented One-phase Single Coil

DC Brushless Motor Design	
Nr. of Motor Poles:	8
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-O)
Bearing System:	Vapo
With Magnetic Levitation System	
Lead Wire:	AWG28, Stripped, Tinned



Technical Specifications



Rated Voltage	
MC25101_:	
12V DC	
Operating Voltage	
MC25101_:	
4,5...13,8V DC	
Dielectric Strength at 65% r. F.:	500V AC for 1 Min.
Insulation Resistance at 500V DC:	>500MOhm
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C



Part Nr.	U _{Rated}	P _{Airflow}	Noise	I	P _{el}	Speed
	[V]	[m ³ /h]	[dBA]	[A]	[W]	[RPM]

MF25101V11000UA99	12	6,45	26	0,050	0,6	14000

P_{Airflow} = Airflow, P_{el} = Rated Power and Current Tolerance, ±15%

Productinformatie

Artikelnummer	F1202510VD
Merk	SUNON
Is on Sale	Nee

