

VENTILATOR 12V/DC VAPOLAGER 25X25X10MM 5,1M3/H 16DB

€ 9,20

Excl. BTW: € 7,60

## Afbeeldingen



## Beschrijving

### Design

Motor:

Patented One-phase Single Coil

DC Brushless Motor Design

Nr. of Motor Poles:	8
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-0)
Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	AWG28, Stripped, Tinned

Technical Specifications

Rated Voltage	
MC25101_:	12V DC
Operating Voltage	
MC25101_:	4,5...13,8V DC
Dielectric Strength at 65% r. F.:	500V AC for 1 Min.
Insulation Resistance at 500V DC:	>500MOhm
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C

Part Nr.	$U_{Rated}$	$P_{Airflow}$	Noise	I	$P_{el}$	Speed
	[V]	[m <sup>3</sup> /h]	[dBA]	[A]	[W]	[RPM]

MF25101V21000UA99	12	5,09	16	0,030	0,36	9600
-------------------	----	------	----	-------	------	------

$P_{Airflow}$  = Airflow,  $P_{el}$  = Rated Power and Current Tolerance,  $\pm 15\%$

## Productinformatie

Artikelnummer	F1202510VE
Merk	SUNON

