

Eijlander Electronics Ede

..... THE BEST IN ELECTRONICS!

Zanderijweg 12,
6717BM Ede
T. 0318-757900

VENTILATOR 5V/DC VAPOLAGER 30X30X6MM 6,2M3/H 15,7DB

€ 8,47

Excl. BTW: € 7,00

Afbeeldingen



Beschrijving

Design

Motor:	Patented One-phase Single Coil
	DC Brushless Motor Design
Nr. of Motor Poles:	8
Frame Impeller:	Filled Thermoplastic PBT (UL94V-0)
Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	AWG28, Stripped, Tinned

Technical Specifications

Rated Voltage:	5V DC
Operating Voltage:	2,5...6V DC
Dielectric Strength at 65% r. F.:	500V AC for 1 Min.
Insulation Resistance at 500V DC:	>500MOhm
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C

Part Nr.	U_{Rated}	$P_{Airflow}$	Noise	I	P_{el}	Speed
	[V]	[m ³ /h]	[dBA]	[A]	[W]	[RPM]
MF30060V21000UA99	5	6,28	15,7	0,072	0,36	7100

$P_{Airflow}$ = Airflow, P_{el} = Rated Power and Current Tolerance, ±15%

Productinformatie

Artikelnummer	F0503006VE
Merk	SUNON

