

VENTILATOR 5V/DC VAPOLAGER 30X30X10MM 9,3M3/H 23DB

€ 9,86

Excl. BTW: € 8,15

Afbeeldingen



Beschrijving

Design

Motor:

Patented One-phase Single Coil

DC Brushless Motor Design

Nr. of Motor Poles:	8
Frame, Impeller:	Filled Thermoplastic PBT (UL94V-0)
Bearing System:	Vapo
	With Magnetic Levitation System
Lead Wire:	AWG28, Stripped, Tinned

Technical Specifications

Rated Voltage	
MC30100_:	5V DC
:	
Operating Voltage	
MC30100_:	2,5...6V DC
Dielectric Strength at 65% r. F.:	500V AC for 1 Min.
Insulation Resistance at 500V DC:	>500MW
Storage Temperature:	-40...+70°C
Operating Temperature:	-10...+70°C

Part Nr.	U_{Rated}	P_{Airflow}	Noise	I	P_{el}	Speed
	[V]	[m ³ /h]	[dBA]	[A]	[W]	[RPM]
MF30100V1100UUA99	5	9,34	23	0,12	0,6	11000

P_{Airflow} = Airflow, P_{el} = Rated Power and Current Tolerance, $\pm 15\%$

Productinformatie

Artikelnummer	F0503010VE
Merk	SUNON

