

VENTILATOR 5V/DC VAPOLAGER 40X40X6MM 9.3M3/H 25.7DB

€ 13,50

Excl. BTW: € 11,16

## Afbeeldingen



## Beschrijving

### Design

|                     |                                    |
|---------------------|------------------------------------|
| Motor:              | Patented One-phase Single Coil     |
|                     | DC Brushless Motor Design          |
| Nr. of Motor Poles: | 4                                  |
| Frame, Impeller:    | Filled Thermoplastic PBT (UL94V-0) |
| Bearing System:     | Vapo                               |
|                     | With Magnetic Levitation System    |
| Lead Wire:          | AWG28, Stripped, Tinned            |

## Technical Specifications

|                                    |                    |
|------------------------------------|--------------------|
| Rated Voltage:                     | 5V DC              |
| Operating Voltage:                 | 2,5...5,5V DC      |
| Dielectric Strength at 65% r. F.:  | 500V AC for 1 Min. |
| Insulation Resistance at 500V DC : | 10MΩ               |
| Storage Temperature:               | -40...+70°C        |
| Operating Temperature:             | -10...+70°C        |

| Part Nr.             | $U_{\text{Rated}}$ | $P_{\text{Airflow}}$ | Noise | I     | $P_{\text{el}}$ | Speed |
|----------------------|--------------------|----------------------|-------|-------|-----------------|-------|
|                      | [V]                | [m <sup>3</sup> /h]  | [dBA] | [A]   | [W]             | [RPM] |
| <b>MF40060V2-A99</b> | 5                  | 9,34                 | 25,7  | 0,065 | 0,33            | 6000  |

$P_{\text{Airflow}}$  = Airflow,  $P_{\text{el}}$  = Rated Power and Current Tolerance, ±15%

## Productinformatie

---

|               |            |
|---------------|------------|
| Artikelnummer | F0504006VC |
| Merk          | SUNON      |

