

MINI LED DRIVER 19-38VDC 1050MA 40W DIMBAAR

€ 29,95

Excl. BTW: € 24,75

Afbeeldingen



Beschrijving

Features

- Independent power supply
- Class II protection, SELV output
- Flicker-free design
- Constant current
- IP20
- Protected against over load, short circuit, over voltage and over temperature
- EN61347-1, EN61347-2-13, EN55015, EN61000-3-2 etc.
- For LED lighting applications
- 5 years warranty

Technical Specifications

Input Voltage:	220...240V AC
Input Inrush Current:	19A
Operating Temperature:	-20...+40°C
Nominal Life-Time (Tc=75°C):	50.000h
Weight:	220g

Part Nr.	U_A	I_A	P_A	I_{RN}	h
	[V]	[mA]	[W]	[mA _{p-p}]	[%]
SLD40-700IL-ES	30...55	700	40	50	87
SLD40-800IL-ES	25...50	800	40	50	87
SLD40-900IL-ES	22...44	900	40	70	86
SLD40-1050IL-ES	22...38	1050	40	70	86

U_A = Output Voltage, I_A = Output Current, P_A = Output Power, I_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	SLD40105IL
Merk	SELF

