


MINI LED DRIVER 15-29VDC 700mA 20W DIMBAAR

€ 19,95

Excl. BTW: € 16,49

Afbeeldingen



Beschrijving

Features

- Independent power supply
- Class II protection, SELV output
- Flicker-free design
- Constant current
- IP20
- Protected against over load, short circuit, over voltage and over temperature
- EN61347-1, EN61347-2-13, EN55015, EN61000-3-2 etc.
- For LED lighting applications

Technical Specifications

| | |
|-----------------------|---------------|
| Input Voltage: | 220...240V AC |
| Input Inrush Current: | 2A |

| | |
|------------------------------|-------------|
| Operating Temperature: | -20...+40°C |
| Nominal Life-Time (Tc=85°C): | 35.000h |
| Weight: | 75g |

| Part Nr. | U_A | I_A | P_A | I_{RN} | h |
|----------------|---------|-------|-------|----------------------|------|
| | [V] | [mA] | [W] | [mA _{p-p}] | [%] |
| SLD20-350IL-ES | 30...54 | 350 | 20 | 50 | 81,8 |
| SLD20-500IL-ES | 20...40 | 500 | 20 | 80 | 80,8 |
| SLD20-700IL-ES | 15...29 | 700 | 20 | 100 | 78,5 |

U_A = Output Voltage, I_A = Output Current, P_A = Output Power, I_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

| | |
|---------------|------------|
| Artikelnummer | SLD20700IL |
| Merk | SELF |

