

GESCHAKELDE VOEDING 3.3V 2.5A 8.2W PRINT MONTAGE

€ 11,95

Excl. BTW: € 9,88

Afbeeldingen



Beschrijving

Features

- Enclosed type for PCB mounting
- Universal input
- Protections: short circuit and over load
- Cooling by free air convection
- Low no load power consumption
- Insulation class II

Technical Specifications

Input Voltage:	85...264V AC (47...440Hz)
	120...370V DC
Input Inrush Current, Max.:	40A
No Load Power Consumption, Max.:	0,1W
Withstand Voltage:	3000V AC
Operating Temperature:	-30...+70°C
Weight:	40g

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
IRM-10-3.3	3,3	0...2,5	8,25	2,5	200	74
IRM-10-5	5	0...2	10	2,5	200	77
IRM-10-12	12	0...0,85	10,2	2,5	200	82
IRM-10-15	15	0...0,67	10,05	2,5	200	82
IRM-10-24	24	0...0,42	10,08	2,5	200	82

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Norms

TÜV EN60950-1, UL60950-1

Productinformatie

Artikelnummer	IRM1003
Merk	MEANWELL

