

LI-ION BATTERIJ LADER 28.6V 0-1.04A MET DC 2.1X5.5MM PLUG

€ 49,95

Excl. BTW: € 41,28

Afbeeldingen



Beschrijving

Features

- 2-stage charger for lead and Li-ion batteries
- Wide input range
- Insulation Class II
- Protections: short circuit/over load/over voltage/ over temp.
- Energy efficiency level VI (DOE)
- Safety standards: UL60950-1, EN60950-1
- EMC standards: EN55014-1 Class B
- 2 years manufacturer warranty

Technical Specifications

Input Voltage:	80...264V AC (47...63Hz)
	113...370V DC
Input Inrush Current, Max.:	110A
Operating Temperature:	-30...+70°C
Weight:	1100g

Part Nr.	U_A	I_A	P_A	U_{RN}	h
	[V]	[A]	[W]	[mV _{p-p}]	[%]
GC30B0P	4,2	4	16,8	50	55
GC30B2P	8,4	3	25,2	80	76
GC30B4P	14,3	2,09	30	100	78
GC30B5P	16,8	1,6	27	100	78
GC30B6P	28,6	1,04	30	150	80

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{RN} = Ripple & Noise, h = Efficiency

Artikelnummer	GC30B6P
Merk	MEANWELL



Productinformatie